



Gulf Formula CX

Catalyst Compatible Passenger Car Motor Oil

Product Description

Gulf Formula CX is superior performance catalyst compatible, mid SAPS (Sulphated Ash, Phosphorous & Sulphur) passenger car motor oil formulated from finest quality synthetic base stocks and state-of-the-art additive technology. It is specially developed for all modern turbocharged, high output gasoline and diesel engines of passenger cars, SUVs, light vans and trucks requiring ACEA C2/C3 quality oils. It is designed to provide protection against Low Speed Pre-Ignition (LSPI) and timing chain wear issues generally observed in latest turbocharged Gasoline Direct Injection (GDI) engines. It provides exceptional cleaning power and wear protection and minimises deposits in engine & turbocharger leading to superior overall performance. It meets the requirements of the latest low emission oil specifications of leading car manufacturers including Mercedes Benz and BMW.

Features & Benefits

- Designed to deliver outstanding performance and protection together with fuel economy benefits
- Latest mid SAPS additive technology prolongs life of exhaust after treatment devices such as Gasoline Particulate Filters (GPF) & Diesel Particulate Filters (DPF) in modern passenger cars
- Special formula helps in protecting the engines from Low Speed Pre-Ignition (LSPI) and Timing chain wear issues observed in latest turbocharged Gasoline Direct Injection (GDI) engines
- Active cleaning agents reduces piston deposits and sludge build-up
- Excellent low temperature fluidity aids cold start and protects against wear at start-up

Applications

- Suitable for use in passenger cars requiring 5W-30, ACEA C3 oils including cars requiring FIAT 9.55535 S3
- Modern gasoline and diesel passenger cars, SUVs, light vans & trucks meeting Euro 6 & prior emission norms requiring API SP or ACEA C2/C3 quality oils
- All gasoline and diesel engines in Mercedes Benz passenger vehicles meeting Euro 6 & prior emission norms and requiring oils meeting MB 229.31/ 229.51/ 229.52
- All BMW gasoline and diesel cars fitted with particulate filters requiring BMW Longlife-04 quality oils
- Also suitable for all diesel and gasoline cars of General Motors requiring GM dexos2™ quality oils

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30
ACEA C2/C3		X
MB 229.31, Opel-Vauxhall OV0401547-G30, OV0401547-D30		X
Has the following Approvals		
API SP, SN PLUS		X
MB-Approval 229.51/ 229.52, BMW Longlife-04		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	11.9
Viscosity Index	D 2270	168
Flash Point, °C	D 92	226
Pour Point, °C	D 97	-42
TBN, mg KOH/g	D 2896	7.5
Density @ 15°C, Kg/l	D 1298	0.84
Sulphated Ash, %wt	D 874	0.70
Phosphorus, %mass	D 4047/ICP	0.071

Gulf Europe - May 2023

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.