



# 4-STROKE OUTBOARD 10W-40

## Product Description:

**4-STROKE OUTBOARD 10W-40** is a premium 4-stroke engine oil specially designed for the most modern high output gasoline power, water cooled outboard / inboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W Catalyst Compatible® (Four Cycle-Water specification).

**4-STROKE OUTBOARD 10W-40** is based on a high quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional shear stability.
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment.
- Good Low temperature fluidity assists easy cold start.
- Active cleaning agents provide superior engine cleanliness

**4-STROKE OUTBOARD 10W-40** exceeds the following performance criteria:

**NMMA FC-W    NMMA FC-W Catalyst Compatible®    API SM**

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	10W-40
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	862
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	91
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	150
Viscosity CCS @-25°C	cP	ASTM D2270	6100
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.1

**Product Nr:** 43281  
**Date Superseded:** -

**Date Issued:** 16-02-2024  
**Revision nr:** -

