



# ATF DX VI

## Product Description:

**ATF DX VI** is a high quality universal fluid based on 100% synthetic base stocks to be used in automatic transmission, torque converters and powersteering of passenger car, light vans and commercial vehicles where a GM Dexron VI specification is required. This product is backwards compatible where DEXRON® III (H), DEXRON® III(G), DEXRON®IIE and DEXRON®IID is been required.

**ATF DX VI** is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

**ATF DX VI** meets the following performance criteria:

## Dexron VI

Property	Unit	Test Method	Typical Value
Color		Visual	RED
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	844
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	27.2
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	5.7
Viscosity Index		ASTM D2270	160
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-48

**Product Nr:** 43240

**Date Superseded:** 22-02-2018

**Date Issued:** 16-12-2019

**Revision nr:** 03

