



CVT FLUID

Product Description:

ATF CVT FLUID is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

ATF CVT FLUID is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation stability.
- Extended drain interval possible.
- Excellent anti-wear, anti-rust and anti-corrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

ATF CVT FLUID exceeds the following performance criteria:

Audi/VW G 052 180

Audi/VW G 052 516

BMW EZL 799A

FCA CVTF+4

GM DEX-CVT

GM CVT

Subaru e-CVTF

Subaru i-CVT F / FG

Toyota TC

Ford Mercon C

Ford M2C928-A

Honda HCF-2

Hyundai/Kia SP CVT-1

MB 236.20

Nissan NS-1/NS-2/NS-3

Subaru High Torque CVTF

Suzuki CVTF 3320

Toyota FE

Daihatsu Ammix CVTF-DC, CVTF-DFE

Ford WSS-M2C933-A

Honda Genuine CVT Fluid

Honda Multi Matic Fluid (HMMF)

Mazda CVTF 3320 / JWS 3320

Mitsubishi Dia Queen CVTF J1 / J4

Subaru Lineartronic CVTF / CVTF-II

Suzuki CVT Fluid Green 1 / 2

Toyota WS (JWS3324)



Property	Unit	Test Method	Typical Value
Color		Visual	Amber
Density @15°C	kg/m ³	ASTM D4052	848.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	34.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	174
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-51

Product Nr: 43250

Date Superseded: 03-10-2023

Date Issued: 31-12-2024

Revision nr: 06