

## INDUSTRIAL GEAR OIL CLP 150

## **Product Description:**

**INDUSTRIAL GEAR OIL CLP 150** is a high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**INDUSTRIAL GEAR OIL CLP 150** is based on high quality mineral base oil in combination with an unique zinc-free additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

**INDUSTRIAL GEAR OIL CLP 150** meets the following performance criteria:

DIN 51517-3 CLP ISO 12925-1 CKD AGMA 9005 E-02

AGMA 9005-F16 David Brown S1.53.101 E AIST 224 (former US Steel 224)

| Property                 | Unit     | Test Method | Typical Value |
|--------------------------|----------|-------------|---------------|
| ISO VG Grade             |          | ISO 3448    | 150           |
| Density@15°C             | kg/m³    | ASTM D4052  | 892           |
| Kin. Viscosity @40°C     | mm²/s    | ASTM D7042  | 149           |
| Kin. Viscosity @100°C    | mm²/s    | ASTM D7042  | 14.4          |
| Viscosity Index          |          | ASTM D2270  | 94            |
| Flash Point COC          | °C       | ASTM D92    | >201          |
| Pour Point               | °C       | ASTM D7346  | -15           |
| FZG Fail Load Stage, min |          | DIN 51354-2 | >12           |
| Total Acid Number        | mg KOH/g | ASTM D664   | <0.5          |

**Product Nr:** 43720 **Date Issued:** 16-12-2019

**Date Superseded:** 18-07-2016 **Revision nr:** 01

