



4-STROKE MARINE ENGINE OIL **25W-40**

Product Description:

4-STROKE MARINE ENGINE OIL 25W-40 is a premium 4-stroke engine oil specially designed for the most modern high output gasoline power, water cooled outboard / inboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W Catalyst Compatible® and various manufacturers like Mercury and Mercruiser marine.

4-STROKE MARINE ENGINE OIL 25W-40 is based on a high quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional shear stability.
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment.
- Good Low temperature fluidity assists easy cold start.
- Active cleaning agents provide superior engine cleanliness

4-STROKE MARINE ENGINE OIL 25W-40 exceeds the following performance criteria:

NMMA FC-W Catalyst Compatible®

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	25W-40
Density@15°C	kg/m ³	ASTM D4052	872.6
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	119.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	113
Viscosity CCS @-10°C	cP	ASTM D2270	4080
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	7.4

Product Nr: 45510

Date Superseded: 05-01-2022

Date Issued: 6-1-2025

Revision nr: 02

