



SNOW MOBILE OIL SYN 2T

Product Description:

SNOW MOBILE OIL SYN 2T is a fully synthetic excellent performance lubricant developed for air & water cooled 2-stroke engines. The special formulation ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions.

SNOW MOBILE OIL SYN 2T is based on a high quality fully synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at very low ambient temperatures.

SNOW MOBILE OIL SYN 2T exceeds the following performance criteria:

API TC
Husqvarna 346

JASO FD

ISO-L-EGD
Husqvarna 372

ROTAX 253



| Property | Unit | Test Method | Typical Value |
|-----------------------|--------------------|-------------|---------------|
| Density@15°C | kg/m ³ | ASTM D4052 | 876.6 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 49.1 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 8.7 |
| Viscosity Index | | ASTM D2270 | 158 |
| Flash Point COC | °C | ASTM D92 | >90 |
| Pour Point | °C | ASTM D7346 | -54 |
| Total Base Number | mgKOH/g | ASTM D2896 | 2.2 |
| Sulphated Ash | %Wt | ASTM D78 | 0.15 |

Product Nr: 42910
Date Superseded: 12-12-2019

Date Issued: 6-1-2025
Revision nr: 04