



# OUTBOARD ENGINE OIL **2T**

**Product Description:**

**OUTBOARD ENGINE OIL 2T** is a high performance ashless 2-stroke engine oil for use in modern cooled outboard engines where NMMA TC-W3 is required

**OUTBOARD ENGINE OIL 2T** is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent lubricity.
- Protection against wear and rust.
- High protection against scuffing and deposit forming.
- Easy mixing and stable mixture even at low temperatures

**OUTBOARD ENGINE OIL 2T** exceeds the following performance criteria:

**NMMA TC-W3®**

Property	Unit	Test Method	Typical Value
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	877.9
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	45.6
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7.1
Viscosity Index		ASTM D2270	114
Flash Point COC	°C	ASTM D92	>90
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D78	0.15

**Product Nr:** 42960  
**Date Superseded:** 24-6-2021

**Date Issued:** 6-1-2025  
**Revision nr:** 05

