



# COMPRESSOR OIL

## VDL 68

### Product Description:

**COMPRESSOR OIL VDL 68** is a high performance ash less air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers.

**COMPRESSOR OIL VDL 68** is suited for reciprocating air-, rotary screw and vane compressors. Also used in circulating oil systems, plain and rolling element bearings, lightly loaded Gear sets, etc

**COMPRESSOR OIL VDL 68** is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Improved equipment reliability, availability and efficiency.
- Low ash and carbon forming tendency ensures improved valve performance.
- Reduced potential for fires and explosions in the discharge systems.
- Exceptional wear and rust protection.
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency.
- Reduces sludge formation and improves life of coalesces.

**COMPRESSOR OIL VDL 68** exceeds the following performance criteria:

**DIN 51506 VBL/VCL/VDL**

**DIN 51503-1 KAA/KE**

**ISO 6521 DAA/DAB/DAG/DAH**



Property	Unit	Test Method	Typical Value
ISO VG Class			68
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	863.7
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	68.6
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.2
Viscosity Index		ASTM D2270	111
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
FZG A/8, 3/90°C		DIN 51354-2	12
Demulsibility @54°C, max	min	DIN 51999	30

**Product Nr:** 43820

**Date Superseded:** 6-11-2024

**Date Issued:** 4-4-2025

**Revision nr:** 05