

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation Yamalube 2-W (For Outboard) W/V

of the mixture

Registration number -

Synonyms None. SDS number A4083

Issue date 22-March-2013

Version number 01
Revision date Supersedes date -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier YAMAHA MOTOR EUROPE N.V.

Address Koolhovenlaan 101

1119 NC Schipol-Rijk, The Netherlands

Telephone +31 (0) 20 654 6000 **Fax** +31 (0) 20 654 6888

e-mail P&Acustomersupport@yamaha-motor.nl

1.4 Emergency telephone

number

+31 (0) 20 654 6000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation does not meet the criteria for classification according to Directive 1999/45/EC as amended.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Physical hazards Not classified for physical hazards. Health

hazards Not classified for health hazards.

Environmental hazards Not classified for hazards to the environment.

Specific hazards

Vapours may form explosive mixtures with air. The harmful effects may increase in used oil.

Main symptoms

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.
Signal word None.

Hazard statements The mixture does not meet the criteria for classification.

Precautionary statements

PreventionNot available.ResponseNot available.StorageNot available.DisposalNot available.Supplemental label informationNot applicable.

Yamalube 2-W (For Outboard) W/V

SDS EU

This Safety Data Sheet complies with the requirements of Regulation (EC) No 453/2010.

CAS-No. / EC No. REACH Registration No.

Notes

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name

Lubricating oils 60 - < 7074869-22-0 649-484-00-0

278-012-2

Classification: DSD: -

CLP: -

10 - < 20 Hydrocarbons, C11-C14, n-alkanes

,isoalkanes,cyclics,<2%aromatics 918-481-9

DSD: Xn;R65 Classification:

CLP: Asp. Tox. 1;H304

Additive 5 - < 10

Classification: **DSD:** R52/53

CLP: Aquatic Chronic 3;H412

DSD: Directive 67/548/EEC CLP: Regulation No. 1272/2008.

Composition comments The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent

> by weight unless ingredient is a gas. Gas concentrations are in percent by volume. Lubricating oil: Contains less than 3 % DMSO extract as measured by IP 346.

SECTION 4: First aid measures

General information First aid personnel must be aware of own risk during rescue.

4.1. Description of first aid measures

Inhalation Move injured person into fresh air and keep person calm under observation. Get medical attention

if any discomfort continues.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention promptly if symptoms occur after washing.

Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere

to affected area. Call an ambulance. Continue flushing during transport to hospital.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open

eyelids wide apart. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low

so that stomach vomit doesn't enter the lungs. Get medical attention.

4.2. Most important symptoms and effects, both acute and

delayed

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

4.3. Indication of any immediate medical attention

Treat symptomatically.

and special treatment needed

SECTION 5: Firefighting measures

General fire hazards Will burn if involved in a fire.

5.1. Extinguishing media

Suitable extinguishing

Extinguish with foam, carbon dioxide, dry powder or water fog.

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture By heating and fire, harmful vapours/gases may be formed.

Yamalube 2-W (For Outboard) W/V

SDS EU 2/8 913260 Version No.: 01 Revision date: -Issue date: 22-March-2013

5.3. Advice for firefighters

Special protective equipment for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Special fire fighting

procedures

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with

water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Stay upwind. Eliminate all sources of ignition. Avoid inhalation of vapours and spray mists. Avoid prolonged and repeated contact. Avoid contact with used oils. Wear appropriate personal

protective equipment. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of

spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up

Remove sources of ignition. Stop the flow of material, if this is without risk. Absorb spillage with non-combustible, absorbent material. In case of spills, beware of slippery floors and surfaces.

6.4. Reference to other

sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Provide adequate ventilation. Avoid inhalation of vapours and spray mists. Avoid prolonged and repeated contact. Avoid contact with used oils. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep containers tightly closed in a cool,

well-ventilated place.

7.3. Specific end use(s)

Engine oil.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Туре	Value	Form	
Lubricating oils (CAS 74869-22-0)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Туре	Value
Lubricating oils (CAS	TWA	5 mg/m3
74869-22-0)		

Czech Republic. OELs. Government Decree 361

Components	Туре	Value	Form	
Lubricating oils (CAS 74869-22-0)	Ceiling	10 mg/m3	Aerosol	
,	TWA	5 mg/m3	Aerosol	

Denmark. Exposure Limit Values

Components	Туре	Value	Form	
Lubricating oils (CAS	TLV	1 mg/m3	Mist.	
74869-22-0)				

Greece. OELs (Decree No. 90/1999, as amended)

Components	Туре	Value	Form
Lubricating oils (CAS	TWA	5 mg/m3	Mist.
74869-22-0)		_	

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Туре	Value	Form
Lubricating oils (CAS 74869-22-0)	Ceiling	5 mg/m3	Mist.

Yamalube 2-W (For Outboard) W/V

SDS EU

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Туре	Value	Form
Lubricating oils (CAS 74869-22-0)	TWA	1 mg/m3	Mist.
reland. Occupational Exposure	Limits		
Components	Туре	Value	Form
Lubricating oils (CAS 74869-22-0)	TWA	0,2 mg/m3	Inhalable fraction.
taly. OELs			
Components	Туре	Value	Form
Lubricating oils (CAS 74869-22-0)	TWA	5 mg/m3	Inhalable fraction.
Lithuania. OELs. Limit Values fo	or Chemical Substances, Gener	al Requirements (Hygiene No	orm HN 23:2007)
Components	Туре	Value	Form
_ubricating oils (CAS 74869-22-0)	STEL	3 mg/m3	Fume and mist.
4009-22-0)	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding)			
Components	Туре	Value	Form
_ubricating oils (CAS 74869-22-0)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms f	or Contaminants in the Workpla	ace	
			Form
Components	Туре	Value	FOIIII
Lubricating oils (CAS) 74869-22-0) Poland. MACs. Minister of Labor	TLV	1 mg/m3	Mist.
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment	TLV	1 mg/m3	Mist.
Lubricating oils (CAS) 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS)	TLV ur and Social Policy Regarding	1 mg/m3 Maximum Allowable Concent	Mist. trations and Intensities in
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type	1 mg/m3 Maximum Allowable Concent Value	Mist. trations and Intensities in Form
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol
Components Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3	Mist. trations and Intensities in Form Aerosol Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Aerosol Form
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Aerosol Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Aerosol Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of well Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace	Mist. trations and Intensities in Form Aerosol Aerosol Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of we	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value	Mist. trations and Intensities in Form Aerosol Aerosol Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupate Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of we Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the go	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA Type STEL TWA Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of we Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the googents	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA Type STEL TWA Type STEL TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of work Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA orkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 5 mg/m3	Mist. trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of work Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA orkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 Itic concerning protection of I Value 1 mg/m3	Mist. Form Aerosol Form Aerosol Aerosol Aerosol Aerosol Form Aerosol Form Aerosol Form Fume and mist.
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of we Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gost	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 5 mg/m3 Itic concerning protection of Items	Mist. trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol Aerosol Form Form Form Aerosol
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupation Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of well Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 Itic concerning protection of I Value 1 mg/m3	Mist. Form Aerosol Form Aerosol Aerosol Aerosol Aerosol Form Aerosol Form Aerosol Form Fume and mist.
Components Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of we Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the go agents Lubricating oils (CAS 74869-22-0) Spain. Occupational Exposure L	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA orkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA imits	1 mg/m3 Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 5 mg/m3 5 mg/m3 5 mg/m3 5 pg/m3 1ic concerning protection of I	Mist. trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol Form Form Fume and mist. Fume and mist.

Yamalube 2-W (For Outboard) W/V

SDS EU

Sweden. Occupational Exposure Limit Values

Components	Туре	Value	Form	
Lubricating oils (CAS 74869-22-0)	STEL	3 mg/m3	Mist.	
	TWA	1 mg/m3	Mist.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs)

Components	Туре	Route	Value	Form
Lubricating oils (CAS 74869-22-0)	Oral	Oral	9,33 mg/kg	

8.2. Exposure controls

Appropriate engineering Provide adequate ventilation. Observe occupational exposure limits and minimise the risk of

controls inhalation of vapours and mist.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

Eye/face protection Risk of splashes: Wear approved safety goggles.

Skin protection

- Hand protection Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is

advisable.

- Other Wear appropriate clothing to prevent repeated or prolonged skin contact.

Respiratory protection In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment

with combination filter (type A2/P2) can be used.

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid. Form Liquid. Colour Purple. Odour Slight.

Odour threshold Not available. Not applicable. pН Melting point/freezing point Not available Initial boiling point and boiling Not available.

range

Flash point

115 °C (239 °F) Cleveland open cup

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability limit - upper 7

(%)

Not available. Vapour pressure Not available. Vapour density Not available. Relative density Insoluble in water. Solubility(ies)

Yamalube 2-W (For Outboard) W/V

SDS EU 5/8 913260 Version No.: 01 Revision date: -Issue date: 22-March-2013

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 200 - 410 °C (392 - 770 °F) (Estimated)

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot available.Oxidizing propertiesNot available.

9.2. Other information

Density 0,865 g/cm³
Pour point -47,5 °C (-53,5 °F)

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Stable at normal conditions.

10.3. Possibility of hazardous

reactions

Will not occur.

10.4. Conditions to avoid Heat, sparks, flames. High temperatures.

10.5. Incompatible materials Halogens. Strong acids. Alkalies. Acidifying substances.

10.6. Hazardous Carbon monoxide.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion May cause discomfort if swallowed.

Inhalation In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and

nausea.

Skin contact Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms Dermatitis.

11.1. Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/irritationMay cause eye irritation.Respiratory sensitisationNo data available.Skin sensitisationNo data available.Germ cell mutagenicityNo data available.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Lubricating oils (CAS 74869-22-0) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity No data available.

Specific target organ toxicity - No data available.

single exposure

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard No data available.

Mixture versus substance Not available.

information

Other information

The harmful effects may increase in used oil.

SECTION 12: Ecological information

12.1. ToxicityThe product contains a substance which is harmful to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.2. Persistence and

degradability

No data available.

12.3. Bioaccumulative potential No data available.

Yamalube 2-W (For Outboard) W/V

SDS EU

Not available. Partition coefficient

n-octanol/water (log Kow)

Not available. **Bioconcentration factor (BCF)** 12.4. Mobility in soil Not available.

Mobility in general The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT

and vPvB assessment Not a PBT or vPvB substance or mixture.

Not available. 12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Do not discharge into drains, water courses or

onto the ground.

Contaminated packaging Since emptied containers retain product residue, follow label warnings even after container is

emptied.

EU waste code 13 02 05*

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

SECTION 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

RID

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

This substance/mixture is not intended to be transported in bulk.

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Authorisations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorisation

Not listed.

Yamalube 2-W (For Outboard) W/V

SDS EU

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Lubricating oils (CAS 74869-22-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Lubricating oils (CAS 74869-22-0)

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Lubricating oils (CAS 74869-22-0)

Directive 94/33/EC on the protection of young people at work

Lubricating oils (CAS 74869-22-0)

Other regulations This Safety Data Sheet complies with the requirements of Regulation (EC) No 453/2010.

National regulations Follow national regulation for work with chemical agents. 15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations DNEL: Derived No-Effect Level.

> PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References **CONCAWE**

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if

available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

R65 Harmful: may cause lung damage if swallowed. H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard

workers and the environment.

Yamalube 2-W (For Outboard) W/V

SDS EU 913260 8/8 Version No.: 01 Revision date: -Issue date: 22-March-2013